



FREQUENCY RESPONSE STEREO MODE

LEFT and RIGHT FRONT Channels, +0, -0.5dB from 20Hz to 20kHz

DOLBY PRO LOGIC IIx MODE and MUSIC MODES

LEFT, CENTER and RIGHT FRONT, LEFT and RIGHT SURROUND and BACK channels, +0, -0.5dB from 20Hz to 20kHz

If SMALL speakers are programmed, the above channels employ high pass filters with a corner frequency of 80Hz and a 12dB per octave roll-off.

DD, DTS, and 8 CHANNEL EXTERNAL INPUT

All channels, +0, -0.5dB from 20Hz to 20kHz

SUBWOOFER

Low pass filtered with an 80Hz corner frequency and 24dB per octave roll-off in all Modes except External.

RATED OUTPUT

2V from all Outputs

OUTPUT IMPEDANCE

Less than 600 Ohms all Outputs

MAXIMUM OUTPUT

8V from all Outputs

TOTAL HARMONIC DISTORTION

All channels, 0.005% from 20Hz to 20kHz

INPUT SENSITIVITY

Line Level: 100mV for 500mV output
Phono: 1mV for 500mV output
Dolby Level: 200mV External Processor
Reference Level: 200mV

SIGNAL-TO-NOISE RATIO, A-WEIGHTED

98dB below rated output

MAXIMUM INPUT SIGNAL

High Level: 6V

INPUT IMPEDANCE:

High Level: 20k Ohms, Phono: 47k Ohms

VOLTAGE GAIN

High Level to Tape Output: 0dB
High Level to Preamp Output: 14dB
Phono to Preamp Output: 54dB

tone CONTROLS

Bass and Treble variable 12dB boost to 12dB cut

POWER REQUIREMENTS

100V, 110V, 120V, 220V, 230V, 240V, 50/60Hz, 65 watts

OVERALL DIMENSIONS (H x W x D) includes feet

9-7/16" (24cm) x 17-1/2" (44.5cm) x 18-3/4" (47.6cm)

WEIGHT

31 lbs. (14.1Kg) net, 46 lbs. (20.9Kg) in shipping carton

FLEXIBLE SET UP

Six customizable music modes which are assignable to any of the 11 inputs.

Easy adjustment from front panel or remote without layered menus.

Separate bass and treble settings for each source.

Fully re-nameable inputs.

A full compliment of balanced XLR or unbalanced outputs.

2 sets of balanced inputs.

AM/FM TUNER OPTION

Add the TM-1 Tuner Module and rediscover how good radio can be with a McIntosh tuner.

VIDEO TRANSCODING

Standard definition video signals can be transcoded up to Component and/or digital HDMI.

MULTI ZONE FLEXIBILITY

Support for two zones of both audio and video.

REMOTE CONTROL

One button operation with all McIntosh products via power and data control. IR and RS 232 compatible for easy interface with third party controllers.

FOR THE CONSUMER'S PROTECTION

In order to ensure the highest level of customer satisfaction, "new" McIntosh products may only be purchased over-the-counter or delivered and installed by an Authorized McIntosh Dealer.

McIntosh products that are purchased over the Internet, by phone or mail order are presumed to be "used" and do not qualify for any McIntosh Warranty. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized Dealer or products that have had their serial number altered or defaced.